



The Chemistry of Cleaning™

ABN 80 004 726 890 | MADE IN AUSTRALIA

VIC 03 9480 3000  
NSW 02 9743 6020  
SA 08 8293 2020  
QLD 07 3274 3438  
WA 08 9249 4566

## Safety Data Sheet

Issued: September, 2016

### Section 1 - Identification of the Material and Supplier

**Chemical nature:** Solvent.  
**Trade Name:** Carpet Spotter B  
**Product Use:** Cleaning solvent. Carpet stain remover.  
**Creation Date:** September, 2016  
**This version issued:** This SDS issued September, 2016 shall remain valid for 5 years unless a new SDS is issued in the meantime. Please contact Agar Cleaning Systems P/L to ensure you have the latest version of this product's SDS.

**Poisons Information Centre: Phone 13 1126 from anywhere in Australia**

#### SUPPLIER DETAILS

Company: Agar Cleaning Systems Pty. Ltd.  
Address: 12-14 Cope Street, Preston, Vic. 3072 AUSTRALIA  
Telephone: 03 9480 3000 Facsimile: 03 9480 5100  
Web: [www.agar.com.au](http://www.agar.com.au) Agar SDS are available from this website.  
Email: [sales@agar.com.au](mailto:sales@agar.com.au)

### Section 2 - Hazards Identification

#### Statement of Hazardous Nature

This product is classified as: F, Flammable. Classified as hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

**SUSMP Classification:** None allocated.

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1123, Butyl acetates



#### GHS Signal word: WARNING

Flammable Liquid – Category 3

Specific Target Organ Toxicity, Central Nervous System – Category 3

#### HAZARD STATEMENT:

H226: Flammable liquid and vapour.

H336: May cause drowsiness and dizziness.

#### PREVENTION

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilation and lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing vapours

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves and eye/face protection.

#### RESPONSE

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTRE or doctor if you feel unwell.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

## STORAGE

P403+P233+P235: Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
P405: Store locked up.

## DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## Emergency Overview

**Physical Description & Colour:** Clear colourless liquid.

**Odour:** Fruity fragrance.

**Major Health Hazards:** -

## Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
n-Butyl acetate	123-86-4	>99	713	950

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## Section 4 - First Aid Measures

### General Information:

You should call the Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** Remove victim from exposure – avoid becoming a casualty. Keep patient warm and rested. If breathing has stopped or becomes laboured give artificial resuscitation. Qualified person may administer oxygen. Seek medical advice.

**Skin Contact:** Remove any contaminated clothing and wash area with soap and water. Seek medical attention in the event of irritation.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, do NOT induce vomiting due to the hazard of solvent aspiration into the lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixtures with air. The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool packages involved in a fire, reducing the chances of an explosion.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, fine water spray can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** 24 °C CC

**Upper Explosion Limit:** 1.2 vol %

**Lower Explosion Limit:** 7.5 vol %

**Autoignition temperature:** 415 °C

**Flammability Class:** Flammable Category 3 (GHS); Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

<b>SWA Exposure Limits</b>	<b>TWA (mg/m<sup>3</sup>)</b>	<b>TWA (ppm)</b>	<b>STEL (mg/m<sup>3</sup>)</b>	<b>STEL (ppm)</b>
n-Butyl acetate	724	150	966	200

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** The information at hand indicates that this product is not harmful and that normally no special skin protection is necessary. However, we suggest that you routinely avoid contact with all chemical products and that you wear suitable gloves (preferably elbow-length) when skin contact is likely.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: butyl rubber.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

## Section 9 - Physical and Chemical Properties:

**Physical Description & colour:** Clear colourless liquid.  
**Odour:** Fruity odour.  
**Boiling Point:** About 126°C at 1013 hPa  
**Freezing/Melting Point:** < -90°C . Liquid at normal temperatures.  
**Volatiles:** 100% VOC  
**Vapour Pressure:** 15 hPa @ 20°C.  
**Vapour Density:** Not known  
**Specific Gravity:** 0.881 g/cm<sup>3</sup> @ 20°C  
**Water Solubility:** Soluble.  
**pH:** No data.  
**Volatility:** No data.  
**Odour Threshold:** No data.  
**Evaporation Rate:** 1.0 (N-Butyl acetate = 1)  
**Coeff Oil/water Distribution:** No data  
**Autoignition temp:** 415°C

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

### Information on toxicological effects:

Acute toxicity	No known significant effects or hazards.
Skin corrosion/irritation	No known significant effects or hazards.
Serious eye damage/irritation	No known significant effects or hazards.
Respiratory or skin sensitisation	No known significant effects or hazards.
Germ cell mutagenicity	No known significant effects or hazards.
Carcinogenicity	No known significant effects or hazards.
Reproductive toxicity	No known significant effects or hazards.
Specific target organ toxicity (STOT)- single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity (STOT)- repeated exposure	Repeated exposure may cause skin dryness and cracking.
Aspiration hazard	No known significant effects or hazards.

## Classification of Hazardous Ingredients

### Ingredient:

N-Butyl acetate

### Health effects:

Flammable liquid and vapour. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

## Potential Health Effects

### Inhalation:

**Short Term Exposure:** Vapour is irritant to mucous membranes and respiratory tract. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness.

**Long Term Exposure:** No data for health effects associated with long term inhalation.

### Skin Contact:

**Short Term Exposure:** Contact with skin can result in mild to moderate irritation. Will have a degreasing action on skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. Can be absorbed through the skin.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short Term Exposure:** Vapour and liquid can cause irritation of the eye; mild irritation at 200 – 300 ppm and more marked at 3300 ppm. Watering and congestion of the eyes can occur at higher concentrations.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Swallowing may result in irritation of the mouth and throat. Swallowing small quantities may result in headache, weakness, dizziness and nausea; swallowing larger amounts may lead to unconsciousness

**Long Term Exposure:** No data for health effects associated with long term ingestion.

**Carcinogen Status:**

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** No significant ingredient is classified as carcinogenic by IARC.

## Section 12 - Ecological Information

This product is readily biodegradable. It will not accumulate in the soil or water or cause long term problems. Expected to not be an environmental hazard.

## Section 13 - Disposal Considerations

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## Section 14 - Transport Information

**Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/MSBC criteria.**

**UN Number:** 1123, n-Butyl acetates

**Hazchem Code:** 3[Y]E

**Special Provisions:** 144

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packaging Group:** II

**Packaging Method:** P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

## Section 15 - Regulatory Information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations.

## Section 16 - Other Information

**This SDS contains only safety-related information. For other data see product literature.**

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO PROVIDE ADDITIONAL INFORMATION. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

**Please read all labels carefully before using product.**

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011) and is Copyright ©.

### Abbreviations and Definitions of terms used:

<	less than
>	greater than
ADG CODE	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
AICS	Australian Inventory of Chemical Substances
CAS	Chemical Abstracts Service (Registry Number)
COD	Chemical Oxygen Demand
deg C	Degrees Celsius
g	gram
g/L	grams per litre
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency

	services especially firefighters
HSIS	Hazardous Substance Information System
IARC	International Agency for Research on Cancer
kg	kilogram
L	Litre
LC50	The concentration of a material (inhaled) that will be lethal to 50% of the test animals.
LD50	The dose (swallowed all at once) which is lethal to 50% of a group of test animals.
m3	Cubic metre
mg	milligram
mg/m3	milligrams per cubic metre
miscible	A liquid that mixes homogeneously with another liquid

# CARPET SPOTTER B

Page 6 of 6

N/A	Not applicable
N/K	Not Known
NIOSH	National Institute for Occupational Safety and Health
non-haz	Non- hazardous
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
PEL	Permissible Exposure Limit
ppb	Parts per billion
ppm	Parts per million

R-Phrase	Risk Phrase
STEL	Short term exposure limit
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
SWA	Safe Work Australia, formerly ASCC and NOHSC
TLV	Threshold Limit Value
TWA	Time Weighted average
UN Number	United Nations (Number)
wt	weight

The information in this Data Sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. As far as lawfully possible, Agar Cleaning Systems accepts no liability for any loss, injury or damage (including consequential loss) suffered or incurred by any person as a consequence of reliance on the information and advice contained herein.

End of SDS