



The Chemistry of Cleaning™

ABN 80 004 726 890 | MADE IN AUSTRALIA

VIC 03 9480 3000
NSW 02 9743 6020
SA 08 8293 2020
QLD 07 3274 3438
WA 08 9249 4566

Safety Data Sheet

Issued: October, 2016

Section 1 - Identification of the Material and Supplier

Chemical nature: Blend of liquid hydrocarbons.
Trade Name: Mop Oil
Product Code: MO5, MO20
Product Use: Treatment for dust-mops. Penetrating oil sealer for porous floors.
Creation Date: October, 2016
This version issued: This SDS issued October, 2016 shall remain valid for 5 years unless a new SDS is issued in the meantime. Please contact Agar Cleaning Systems P/L to ensure you have the latest version of this product's SDS.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

SUPPLIER DETAILS

Company: Agar Cleaning Systems Pty. Ltd.
Address: 12-14 Cope Street, Preston, Vic. 3072 AUSTRALIA
Telephone: 03 9480 3000 Facsimile: 03 9480 5100
Web: www.agar.com.au Agar SDS are available from this website.
Email: sales@agar.com.au

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. F, Flammable. Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: Class 3: Flammable liquids.

UN Number: 1993, FLAMMABLE LIQUID, N.O.S.



GHS Signal word: DANGER

Flammable liquid - Category 3
Aspiration hazard - Category 1
Skin irritation – category 3
Aquatic toxicity (Chronic) – category 2
Aquatic toxicity (acute) – Category 2

HAZARD STATEMENT:

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H316: Causes mild skin irritation.
H411: Toxic to aquatic life with long-lasting effects

PREVENTION

P102: Keep out of reach of children.
P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical ventilating, lighting and other equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P262: Do not get in eyes, on skin, or on clothing.
P264: Wash contacted areas thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE phone Australia 131 126 or doctor.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P362: Take off contaminated clothing and wash before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation occurs: Get medical attention.

P332+P313: If skin irritation occurs: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

P391: Collect spillage.

STORAGE

P405: Store locked up.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Emergency Overview

Physical Description & Colour: Clear colourless liquid.

Odour: Characteristic hydrocarbon odour.

Major Health Hazards: skin irritant, if aspirated, may cause lung damage.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Naphtha (petroleum), hydrodesulfurised heavy	64742-82-1	>60	not set	not set
Distillates (petroleum), hydrotreated light paraffinic	various	10-<30	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call the Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If irritation is experienced, remove victim from area and allow to breath fresh air. If irritation persists, call a doctor or poisons information centre.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: 38°C (Cleveland open Cup) ASTM D 92

Upper Flammability Limit: 5-7%

Lower Flammability Limit: 0.7%

Autoignition temperature: 210°C

Flammability Class: Flammable Category 3 (GHS); Flammable (AS1940)

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Nitrile, neoprene,. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: nitrile, neoprene,.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Clear colourless liquid.
Odour:	Characteristic hydrocarbon / kerosene odour.
Boiling Point:	Approximately 160-240°C at 100kPa.
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	>50% VOC
Vapour Pressure:	About 0.7kPa at 20°C
Vapour Density:	4.5 (air = 1) 15°C
Specific Gravity:	0.80 at 20°C
Water Solubility:	Insoluble.
pH:	Not applicable.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	About 0.16 (n-butyl acetate = 100)
Coeff Oil/water Distribution:	No data
Autoignition temp:	Typically 230°C or higher

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Information on toxicological effects:

Acute toxicity	No known significant effects or hazards.
Skin corrosion/irritation	May be a mild irritant.
Serious eye damage/irritation	No known significant effects or hazards.
Respiratory or skin sensitisation	No known significant effects or hazards.
Germ cell mutagenicity	No known significant effects or hazards.
Carcinogenicity	No known significant effects or hazards.
Reproductive toxicity	No known significant effects or hazards.
Specific target organ toxicity (STOT)- single exposure	No known significant effects or hazards.
Specific target organ toxicity (STOT)- repeated exposure	No known significant effects or hazards.
Aspiration hazard	May be fatal if swallowed and enters airways.

Classification of Hazardous Ingredients

Ingredient:

Naphtha (petroleum), hydrodesulfurised heavy (kerosene):

Health effects:

A summary of white spirit- type hydrocarbons can be found at <http://www.inchem.org/documents/ehc/ehc/ehc187.htm>

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea. Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure.

Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few ml of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30ml may be fatal.

Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reportings, the relevance of these findings is unclear. Acute Oral Toxicity: Low, LD50 > 5000 mg/kg, Rat.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity but are CNS depressants and have a disinhibiting euphoric effect.

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product is believed to be mildly irritating, but unlikely to cause anything more than mild discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

Insufficient data to be sure of status.

Biodegradation is expected to be the primary fate process for aliphatic hydrocarbons in soil and water. The rate and extent of biodegradation are dependent on the ambient temperature, the presence of a sufficient number of microorganisms capable of metabolizing the hydrocarbons and the concentration of white spirit in or on the soil or water.

Biodegradation of C₇ to C₁₂ hydrocarbons is expected to be significant under environmental conditions favourable to microbial oxidation. Naturally occurring hydrocarbon-degrading microorganisms have been isolated from polluted soil and, to a lesser extent, non-polluted soil.

The low water solubility and moderate vapour pressure of white spirit (Stoddard solvent) suggest that volatilization and subsequent photo-oxidation are important processes for abiotic degradation in the atmosphere.

The octanol/water partition coefficient (log Pow) of white spirit (17% v/v aromatics) has been found to be 3.5 to 6.4. This indicates a moderate potential for bioaccumulation by organisms from water and a likelihood of partitioning to fat within organisms.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1993, FLAMMABLE LIQUID, N.O.S.

Hazchem Code: •3Y

Special Provisions: 223, 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packing Group: III

Packing Instruction: P001, IBC03, LP01

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO PROVIDE ADDITIONAL INFORMATION. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011) and is Copyright ©.

Abbreviations and Definitions of terms used:

<	less than
>	greater than
ADG CODE	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
CAS	Chemical Abstracts Service (Registry Number)
COD	Chemical Oxygen Demand
deg C	Degrees Celsius
g	gram
g/L	grams per litre
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
HSIS	Hazardous Substance Information System
IARC	International Agency for Research on Cancer
kg	kilogram

L	Litre
LC50	The concentration of a material (inhaled) that will be lethal to 50% of the test animals.
LD50	The dose (swallowed all at once) which is lethal to 50% of a group of test animals.
m3	Cubic metre
mg	milligram
mg/m3	milligrams per cubic metre
miscible	A liquid that mixes homogeneously with another liquid
N/A	Not applicable
N/K	Not Known
NIOSH	National Institute for Occupational Safety and Health
non-haz	Non- hazardous
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
PEL	Permissible Exposure Limit

ppb	Parts per billion
ppm	Parts per million
R-Phrase	Risk Phrase
STEL	Short term exposure limit
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons

SWA	Safe Work Australia, formerly ASCC and NOHSC
TLV	Threshold Limit Value
TWA	Time Weighted average
UN Number	United Nations (Number)
wt	weight

The information in this Data Sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. As far as lawfully possible, Agar Cleaning Systems accepts no liability for any loss, injury or damage (including consequential loss) suffered or incurred by any person as a consequence of reliance on the information and advice contained herein.

End of SDS.