

MASTERPIECE

Floor Sealer Finish

Page I of 2

Product Data Sheet

Product Code: MAS Issued: December 12, 2023

What is Masterpiece?

MASTERPIECE is a high-solids, all-in-one floor sealer and polish. It is extremely durable and long-lasting even under heavy foot traffic.

Key Benefits

- ✓ MASTERPIECE works well on all types of sealable floor.
- ✓ All-in-one sealer and polish.
- ✓ Masterpiece holds its gloss well and is suitable for floors that are not buffed.
- ✓ Highly durable so film lasts longer.
- ✓ Wet-look gloss.
- ✓ High solids fewer coats required.
- ✓ Lays smoothly and effortlessly off the mop.
- ✓ Easy to re-coat simplifies periodic maintenance.

How Does It Work?

MASTERPIECE is a long-lasting acrylic floor polish with excellent wear resistance and durability. It has been formulated to reach very high gloss levels with gas-powered buffing at ultra-high speeds but is equally suited to low-moderate speed buffing. MASTERPIECE is also an ideal basecoat product to go under softer acrylic polishes. MASTERPIECE will provide a glossy finish which will hold its shine much longer than conventional polishes. It has an especially high resistance to abrasion and can withstand heavy traffic levels without wearing out.

For Use On...

MASTERPIECE is a non-slip product designed for application to vinyl, timber and stone floors. (Note: Ceramic tiles are usually not porous enough for acrylic polishes to bond to successfully. Always pre-test the polish on ceramic tiles before applying to the entire floor. Lay 2 coats on one tile. When dry, stick adhesive packaging tape across the tile then rip it off. If the polish has remained in place, it will be safe to use. If it comes off, the tiles cannot be sealed.)

Acrylic sealers, like MASTERPIECE, are not suitable for use on non-porous ceramic or porcelain tiles. Before attempting to seal such ceramic tiles, pre-test the sealer before applying it to the entire floor. To do this, lay two coats of MASTERPIECE on one tile. When dry, stick adhesive packaging tape across the tile, press it down and then rip it off. If the sealer remains in place bonded to the tile, it is safe to use. If the polish peels off, the tiles cannot be sealed with MASTERPIECE. Instead, STONE BLOCK can be used to seal this type of surface.

Technical Data Properties



COLOUR – Milky white liquid ODOUR – Faint ammonia odour pH = 8.0 - 9.0

REMOVABILITY – Fully strippable COVERAGE - 40 – 50 sq metres per litre

VOC Content:

MASTERPIECE contains less than 2 grams of Volatile Organic Compounds per litre. MASTERPIECE therefore complies with 'green' standards which require the VOC content to be less than 7% (ie., 70 grams per litre).

Environmental Care



MASTERPIECE conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. MASTERPIECE is a non-

flammable water-based product. MASTERPIECE containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Ouality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements". First Certified: 30 April 1996 SAI Certificate No.: QEC7358

Application

- Remove adhesive, built-up polish or wax and other soilage using ULTRASTRIP, DEMOLISH or STR-36. New floors should always be stripped prior to sealing. Whilst a new floor looks clean, it is covered in a protective film added at the time of manufacture. New floor polish will not adhere to this film, so it must be stripped.
- Rinse floor, allow to dry, then fringe-mop to remove dust.
- First mop on 2-4 coats of MASTERPIECE allowing 20-40 minutes to dry between coats.

(Continued page 2)

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.





MASTERPIECE

Floor Sealer Finish

Page 2 of 2

Product Data Sheet

Product Code: MAS Issued: December 12, 2023

- ➤ Maintain floor by cleaning with AUTOSCRUB, SYMPOL or SCRUB 'N' SHINE and dry-buffing (for machines from 1000 to 2000+ rpm) or spray-buffing (for machines from 450 to 1000 rpm). Because MASTERPIECE is very tough, the more aggressive natural hair fibre pads may be used to achieve optimal repair of the scratching caused by everyday foot traffic. This will ensure a shiny, beautiful and long-wearing coating.
- ➤ Do not apply any polish to a very cold floor (9°C or less).

Available in: 5L, 20L