

What is Matte Finish?

MATTE FINISH is a tough, hard-wearing, water-based floor polish that dries to a low-sheen finish. It will protect floors and cut down on sun-glare, and is fully strippable.

Key Benefits

- ✓ MATTE FINISH dries to a non-reflective, very low-sheen coating.
- ✓ MATTE FINISH is clear and colourless.
- ✓ MATTE FINISH is non-slip when dry.
- ✓ MATTE FINISH is a hard-wearing, tough coating that will last well even under heavy traffic.
- ✓ MATTE FINISH makes it easier to produce a uniform, streak-free coating.

How Does It Work?

MATTE FINISH is a low-sheen, acrylic floor polish with maximum toughness and mark-resistance. It is fully strippable, so coatings can be replaced whenever desired. This is a major benefit in hospitals and nursing homes. Many architects also specify low-sheen floor coatings in new buildings because they reduce glare and impart a softer look to the interior spaces.

For Use On...

Buildings where sun-glare would be uncomfortable, MATTE FINISH is excellent because it will minimise reflections and glare. MATTE FINISH is suitable for applications to vinyl, timber, stone, terrazzo and concrete.

Acrylic sealers, like 3D-GLOSS, are not suitable for use on non-porous ceramic or porcelain tiles. Before attempting to seal such ceramic tiles, pre-test the sealer before applying it to the entire floor. To do this, lay two coats of 3D-GLOSS on one tile. When dry, stick adhesive packaging tape across the tile, press it down and then rip it off. If the sealer remains in place bonded to the tile, it is safe to use. If the polish peels off, the tiles cannot be sealed with 3D-GLOSS. Instead, STONE BLOCK can be used to seal this type of surface.

Technical Data

Properties



COLOUR – Milky off-white liquid
ODOUR – Faint ammonia odour
pH = 8.0 – 9.0
Coverage: 40 – 50 sq metres per litre.

Environmental Care



MATTE FINISH conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. MATTE FINISH is water-based, hydrocarbon-free and non-flammable. MATTE FINISH containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Slip Resistance

MATTE FINISH passes the Slip Resistance Test under dry conditions as specified in AS 4663-2013. It gives a mean Dynamic Coefficient of friction of 0.75.

Application

- Remove adhesive, built-up polish or wax and other soilage using ULTRA STRIP, DEMOLISH or STR-36. New floors should always be stripped prior to sealing. Whilst a new floor looks clean, it is covered in a protective film added at the time of manufacture. New floor polish will not adhere to this film, so it must be stripped.
- Rinse floor, allow to dry, then fringe-mop to remove dust.
- **STIR** the polish before use with a flat stirrer. There may be some settling upon storage.
- Mop on 3-5 coats of MATTE FINISH allowing 20-40 minutes to dry between coats, then allow to harden overnight.
- Maintain floor by cleaning with AUTOSCRUB. Do not buff the floor.
- Worn areas should be restored by scrubbing thoroughly and then applying a fresh coat of MATTE FINISH to the worn area.

(Continued on Page 2)

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.



The Chemistry of Cleaning™

MATTE FINISH

Low Sheen Sealer

Page 2 of 2

Product Data Sheet

Product Code: MAT

Issued: December 13, 2023

- After a long period in heavy traffic areas (typically 6 months to 1 year), the film may become worn down and/or discoloured. If this happens, strip the film off with ULTRASTRIP, rinse, and then apply a new film of 3-5 coats of MATTE FINISH.
- Do not apply any polish to a very cold floor (9°C or less).

Available in: 5L, 20L

Dispensing Accessories:

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.



MELBOURNE
Agar Cleaning Systems P/L
12-14 Cope Street
Preston VIC 3072
Ph: (03) 9480 3000

ADELAIDE
Agar Cleaning Systems P/L
Unit 1, 138-140 Ashley Street
Underdale SA 5032
Ph: (08) 8293 2020

BRISBANE
Agar Cleaning Systems P/L
Unit 14, 28 Bangor Street
Archerfield QLD 4108
Ph: (07) 3274 3438

SYDNEY
Agar Cleaning Systems P/L
U3/68-72 Asquith Street
Silverwater, NSW, 2128
Ph: (02) 9743 6020

PERTH
Briskleen Supplies
38 Mulgool Road
Malaga WA 6090
Ph: (08) 9249 4566